

T1055III TRENCHER



TEC® PLUS ELECTRONIC CONTROL SYSTEM.
The operating system communicates with multiple control modules located throughout the machine for real-time performance data and advanced troubleshooting capabilities.



ROTARY POWER TRENCHER DRIVE MOTOR.
A rotary power trencher drive motor and splined headshaft produce a lower speed and higher torque which provide superior ground penetration and low chain wear for better production results.



ELEVATING ROPM CAB. The elevating rollover protective module cab features LEXAN® glass, filtered and pressurized air, heating and air-conditioning. The cab's vantage point allows a virtually unrestricted view of the boom, trench and conveyor.



VANTAGE TRACK. Relax in the confidence that your investment is protected and your entire closed loop hydrostatic system is covered with either a 3-year/3000-hour or 5-year/5000-hour Extended Care Service program.



TERRAIN LEVELER® SURFACE EXCAVATION MACHINE ATTACHMENT.
The T1055III has a chain drive Terrain Leveler attachment option for large rock excavation applications including surface mining, overburden removal, site preparation and road demolition.



FULL FUNCTION REMOTE CONTROL.
The T1055III is available with a wireless remote control that can provide full operator function remotely.

T1055III TRENCHER

GENERAL DIMENSIONS

Approach angle: 16°

Height: 11.3' (3.4 m)

Length range: 32.2' – 40.8' (9.8 m – 12.4 m)

Weight range (tractor plus trencher attachment): 105,000 lb – 124,000 lb (47,627.2 kg – 56,245.5 kg)

Width range: 9.7' – 10.2' (2.9 m – 3.1 m)

ENGINE

Make and model: Caterpillar C13 ACERT

Gross horsepower: 415 hp (310 kW)

Engine rpm: 2100

Fuel consumption @ full load: 20.9 gph (79.1 L/hr)

TRACKS

Ground pressure: 9.4 psi – 13.9 psi (64.8 kPa – 95.8 kPa)

Tilt track with Auto Level available: No

Track length: 14.7' (4.5 m)

Track pad type: Single or double grouser

Track pad width: 24" or 30" (61 cm or 76.2)

Track size: D7G

Travel speed max: 124 fpm (37.8 m/min)

Service brakes: Hydrostatic

CONVEYOR

Belt width: 30" (76.2 cm)

Max conveyor belt speed: 1070 fpm (326.1 m/min)

Conveyor belt style: Cleated or finger-type

Conveyor length: 9' or 14' (2.7 m or 4.3 m)

Conveyor shift available: Yes

Conveyor shift distance: 15" or 65" (38 cm or 165.1 cm)

Conveyor style: Curved

Discharge direction: Right or left

CAB

Air conditioner/heater: Yes

Air suspension seat: No

AM/FM stereo with weather band: Yes

Elevating: Yes

Pressurized/Filtered air: Yes

Rollover protective module (ROPM): Yes

Level II FOPS: Yes

TRENCHER ATTACHMENT

Boom depth options: 6', 8', 10', 12' or 14' (1.8 m, 2.4 m, 3 m, 3.7 m or 4.3 m)

Boom top rollers: Yes

Chain speed range: 316 fpm – 714 fpm (96.3 m/min – 217.6 m/min)

Cutting width range: 28" – 42" (71.1 cm – 106.7 cm)

End idler diameter: 40" or 50" (101.6 cm or 127 cm)

CHAIN DRIVE TERRAIN LEVELER ATTACHMENT

Weight (tractor plus attachment): 127,000 lb (57,606.2 kg)

Max cutting depth: 32" (81.3 cm)

Cutting width: 132" (335.3 cm)

Drum tilt available: No

Max drum speed rpm: 59

Laser and GPS acceptable: Yes

Digging chain size: 4501

OPTIONS

Loadout conveyor

Terrain Leveler attachment

Remote control