

Vermeer®

AXIS™ GB812

Guided Boring System



On-grade trenchless installation system

The AXIS guided boring system offers more versatility and flexibility than other sewer and water installation methods, giving you more options to complete on-grade sewer and water installations with pinpoint accuracy.



GB812 Specifications

Rack Power Unit

General Weights and Dimensions

Length: 96" (244 cm)
Width: 77.5" (197 cm)
Height: 96" (244 cm)
Weight: 10,800 lb (4899 kg)

Power

Make/model: John Deere 4045HF
Horsepower (gross): 140 hp (104 kW)
Rated rpm: 2400
Tier rating: Tier 3

Fluid Capacities

Engine oil (including filter): 15.5 qt (14.7 L)
Fuel tank: 79 gal (300 L)
Hydraulic reservoir: 53 gal (201 L)

Rack

General Weights and Dimensions

Length: 134" (340.4 cm)
Width: 33.6" (85 cm)
Height: 60" (152 cm)
Weight: 4500 lb (2041 kg)

Operational

Max spindle torque:
192 rpm: 3030 ft-lb (4108 Nm)
129 rpm: 4550 ft-lb (6169 Nm)
97 rpm: 6070 ft-lb (8229 Nm)
Thrust: 38,000 lb (169 kN)
Pullback: 38,000 lb (169 kN)
Bore diameter: 13.5" (34.3 cm)

Vacuum Power Unit

General Weights and Dimensions

Length: 163" (414 cm)
Width: 87" (221 cm)
Height: 86" (218 cm)
Weight (wet): 22,000 lb (9979 kg)

Power

Make/model: John Deere 6068HF
Horsepower (gross): 250 hp (186 kW)
Rated rpm: 2200 rpm
Tier rating: Tier 3

Operational

Dry air rating: 3200 cfm (90.6 m³/min)
at 20 in. Hg (508 torr)
Moist air rating: 3400 cfm (96 m³/min)
at 26 in. Hg (660.4 torr)

Fluid Capacities

Engine oil (including filter): 33 qt (31 L)
Fuel tank: 115 gal (435 L)
Hydraulic reservoir: 31 gal (117 L)

Drilling Fluid System

Max flow: 25 gpm (94.6 L/min)
Max pressure: 1200 psi (83 bar)

Safety

Falling object protection: Yes
Remote lockout: Yes
Strike alert: Yes

Vacuum Tank

800 gal (3028 L) tank option

Length: 100" (254 cm)
Width: 100" (254 cm)
Height: 96" (244 cm)
Weight (dry): 2500 lb (1134 kg)

2000 gal (7571 L) tank option

Length: 135" (342.9 cm)
Width: 100" (254 cm)
Height: 96" (244 cm)
Weight (dry): 4000 lb (1814 kg)

Drill Head

Length: 78.7" (199.9 cm)
Diameter (max): 13.5" (34.3 cm)
Weight: 720 lb (327 kg)

Drill Casing

Length: 78.7" (199.9 cm)
Diameter: 12" (30 cm)
Weight: 410 lb (186 kg)
Weight (box with 6 segments of drill casing):
2976 lb (1350 kg)

Laser

Make/model: AGL Gradelight



Vermeer Corporation
1210 Vermeer Road East
P.O. Box 200
Pella, Iowa 50219 U.S.A.
Phone: (641) 628-3141
Fax: (641) 621-7773

Vermeer EMEA
(Europe, Middle East, Africa and CIS)
P.O. Box 323
4460 AS Goes
the Netherlands
Phone: +31 113 272700
Fax: +31 113 272727

Vermeer Asia Pacific
48 Toh Guan Road East
#01-105 Enterprise Hub
Singapore 608586
Phone: +65 6516 9560
Fax: +65 6515 9218



www.vermeer.com

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your Vermeer dealer for more information about machine specifications. Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation. VERMEER, the VERMEER LOGO, and AXIS are trademarks of Vermeer Manufacturing Company in the United States and / or other countries. © 2009 Vermeer Corporation. All Rights Reserved.